

FLASH FREE® ELECTRICAL DEGREASER

EL™ 848



Energized Electrical Degreaser:
Energized Equipment use only.



Nonfood Compounds Program Listed
(K2 Rated) (Registration # 115070)



Dielectric Strength 37,000 Volts



Non-Flammable



Evaporation Rate: Fast



KB Value (Cleaning Power) 129



HMIS Rating:
Hazard (2) • Flammability (0) • Reactivity (0)

- Non-flammable, non-corrosive
- Replaces 1,1,1 Trichloroethene
- Leaves no residue



PRESERVE. PROTECT. PREVENT.™

Sprayon® EL™ 848 Flash Free® Electrical Degreaser is a non-flammable, fast evaporating cleaner that penetrates instantly to remove the dirt, oil, grease, wax and other foreign materials that can decrease the life of electrical components & cause costly downtime. Degreases more thoroughly & several times faster than alkaline cleaners. Excellent for degreasing aluminum, cleaning sheet & strip steel prior to galvanizing. Equipped with a high delivery valve for cleaning efficiency, extension tubes are also included for hard-to-reach areas.

USES

- Electric motors
- Generators
- Air tools
- Brakes
- Clutches
- Chains
- Sprockets
- Wire rope
- Dies • Molds
- Relays • Locks
- Radar equipment
- Material handling equipment
- Air conditioners



EL848

© 2010 Sprayon® Products Made in U.S.A.

ELECTRICAL & ELECTRONIC

APPLICATION

Product should be sprayed in a well ventilated area. Shake well before using. Sprays best at room temperature (70°F). Hold can in upright position for best spray pattern. Use extension tube for pinpoint application. NOTE: May harm certain plastics, elastomers and air-dry painted surfaces. Test product on non-essential similar material prior to application.

PROPERTIES

APPEARANCE: Clear Volatile Liquid
ODOR: Mild Solvent
PROPELLANT: CO2
WT./GAL.: 14.04
SPECIFIC GRAVITY: 1.45
EVAPORATION RATE: Fast
KB VALUE (Cleaning Power): 129
DIELECTRIC STRENGTH: 37,000
PLASTIC SAFE: Most plastics, but test substrate first
H.A.P.S. (Hazardous Air Pollutants): No %
VOC AEROSOL: 98%
V.O.C. COMPLIANT CALIFORNIA: Yes
V.O.C. COMPLIANT OTC STATES: Yes
FLAMMABLE: No
FLASH POINT: N/A
HAZARD RATING: 2,0,0
SHELF LIFE: 3 years from date of manufacturer.

PERFORMANCE

- NSF Registration Number 115070, K2 Rated
- No residue
- Non-corrosive
- Replacement for 1,1,1 Trichloroethene
- Equipped with an extension tube for hard-to-reach areas

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

PACKAGING

Stock #: S00848
UPC Code: 075577908486
Fill Wt: 13 oz.
Per Case: 12
Carton Dimensions:
L 10-7/8" x W 8-3/16" x H 8"

Stock #: S20848
UPC Code: 075577208487
Fill Wt: 17 oz.
Per Case: 12
Carton Dimensions:
L 10-7/8" x W 8-3/16" x H 9-5/8"

RESOURCES

MSDS/EDS/PRODUCT DATA
SHEETS: www.paintdocs.com
CUSTOMER SERVICE: 1-800-777-2966
TECHNICAL INFORMATION: 1-800-251-2486



Distributed by:

Lawson Products, Inc.

To order these and other products, contact us:
866-529-7664 lawsonproducts.com



Sprayon® Products

101 Prospect Ave. NW
Cleveland, OH 44115
www.Sprayon.com
1-800-777-2966