

Issue date 13-Jul-2018

Revision date 14-Jun-2019

Revision Number 2

1. IDENTIFICATION**Product identification**

Product identifier Drummond™ Burn-Out Oven and Grill Cleaner

Other means of identification 1508553

Recommended use Cleaner

Restrictions on use For industrial use only

Supplier

Corporate Headquarters:
Drummond™, A Lawson Brand
Lawson Products, Inc.
8870 W. Bryn Mawr Ave., Suite 900
Chicago, IL 60631
(866) 837-9908

Canadian Distribution Center:
Lawson Canada
7315 Rapistan Court
Mississauga, ON L5N 5Z4
(800) 323-5922

24 Hour Emergency Phone Number (888) 426-4851 (Prosar)

Website <https://www.lawsonproducts.com>

2. HAZARD(S) IDENTIFICATION

Hazard Classification This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS 2015 and GHS Regulations.

Acute toxicity - Oral	Category 3
Acute toxicity - Inhalation	Category 4
Skin corrosion/irritation	Category 1
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (single exposure)	Category 3
Corrosive to metals	Category 1

Symbol

Signal word DANGER

Hazard statements H290 - May be corrosive to metals

H301 - Toxic if swallowed
H314 - Causes severe skin burns and eye damage
H332 - Harmful if inhaled
H335 - May cause respiratory irritation

Precautionary statements

General

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P103 - Read label before use.

Prevention

P234 - Keep only in original container
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing and eye/face protection
P264 - Wash hands thoroughly after handling
P270 - Do not eat, drink or smoke when using this product

Response

General

P321 - For Specific treatment see section 4 of this sds

Eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention

Skin

Take off contaminated clothing and wash before reuse.
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash it before reuse
IF ON SKIN: Wash with plenty of water and soap

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Ingestion

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Fire

Use CO2, dry chemical, or foam
In case of fire: Use water spray to extinguish

Spill

P390 - Absorb spillage to prevent material damage

Storage

Store in a well-ventilated place. Keep container tightly closed
Protect from sunlight. Store in a well-ventilated place

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazard(s) Not Otherwise Classified (HNOC)

None known.

Physical Hazards Not Otherwise Classified (PHNOC)

None known.

Unknown acute toxicity

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS 2015 and GHS Regulations.

Composition Mixture.

Chemical name	CAS-No	Weight %
Water	7732-18-5	>70
Potassium hydroxide	1310-58-3	8-15
Diethylene glycol monomethyl ether	111-77-3	3-10
Sodium Citrate	6132-04-03	3-5
Arsenic	7440-38-2	<0.3

4. FIRST-AID MEASURES

Necessary first-aid measures

General Information	After first aid, IMMEDIATELY seek appropriate in plant, paramedic or community medical support.
Inhalation	If symptoms persist, call a physician. Move to fresh air in case of accidental inhalation of vapours or spray mist. If not breathing, give artificial respiration.
Ingestion	Rinse mouth. Call a physician immediately.
Skin contact	Wash off immediately with soap and plenty of water. Remove and wash contaminated clothing before re-use. Seek medical attention if irritation persists.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Seek medical attention if irritation persists.
Most important symptoms (acute)	Nasal irritation. Nausea. Dizziness. Coughing. Headache. Shortness of breath. Weakness. Face discoloration. Causes eye irritation. Irritating to mouth, throat and stomach.
Most important symptoms (over-exposure)	Not available.
Indication of any immediate medical attention and special treatment needed	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	Water spray. Dry chemical. Carbon dioxide (CO2). Alcohol resistant foam.
Unsuitable extinguishing media	Dilution with water creates heat.
Specific hazards	Formation of toxic gases is possible during heating or in case of fire. Nitrogen oxides (NOx). Product may react with some metals (Aluminum, Zinc, Tin) to release hydrogen gas.
Special protective equipment for fire-fighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Use personal protection recommended in Section 8. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. See information in section 7 for safe handling. Keep unnecessary people away, isolate hazard area and deny entry. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area).
--	--

**Methods and materials
for containment and
cleaning up**

Ventilate the area. Keep unnecessary and unprotected personnel from entering the area.

Use clean non-sparking tools to collect absorbed material. Stop leak if you can without risk. Small Spill: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. For large spills, provide diking or other appropriate containment to keep material from spreading. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Do not use water to flush spill area. Neutralize remaining spilled material with a dilute solution of acid if the spilled material is an alkaline or a dilute solution of caustic if the spilled material is acidic. Clean up residue with soap and water. Do not flush into surface water or sanitary sewer system. Report spills as required by local and federal regulations.

7. HANDLING AND STORAGE

**Precautions for
safe handling**

Handle with special care. Do not get in eyes, on skin, or on clothing. Harmful if absorbed through the skin or inhaled. Harmful if swallowed. Wear personal protective equipment. Wash thoroughly after handling. Remove contaminated clothing and footwear. Do not breathe dust/fume/gas/mist/vapors/spray. Use with adequate ventilation. Do not ingest. Do not cut, drill, grind, or weld near containers. Keep the container closed when not in use. Never use pressure to empty. Always open containers slowly to allow any excess pressure to vent. Vapors are combustible to open flames. Use in an area that will allow for evaporation or run off. Prevent contamination of soil, drains and surface waters.

**Conditions for safe
storage, including any
incompatibilities**

Keep away from sources of heat and direct sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep from freezing. Do not store in unlabeled or mislabeled containers. Keep container closed when not in use. Empty containers retain product residue and can be hazardous. Observe label precautions. Keep out of reach of children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical name	OSHA PEL (TWA)	ACGIH OEL (TWA)	NIOSH - TWA
Water	-	-	-
Potassium hydroxide	-	2 mg/m ³ Ceiling	-
Diethylene glycol monomethyl ether	-	-	-
Sodium Citrate	-	-	-
Arsenic	10 µg/m ³ TWA	0.01 mg/m ³ TWA	-

**Appropriate engineering
controls**

Ensure adequate ventilation. Use general ventilation and use local exhaust, where possible, in confined or enclosed spaces. Provide general or local exhaust ventilation systems using corrosive resistant materials to maintain airborne contaminants below any recommended or standard occupational exposure limits. Local exhaust ventilation is preferred because it prevents contamination dispersion into the work area by controlling it at its source. Engineering controls are recommended. See ANSI Z43.1. Refer to OSHA 29 CFR 1910.94. Ensure that eyewash stations and safety showers are close to the workstation location.

**Individual protection measures,
such as personal protective
equipment**

Eye protection

If splashes are likely to occur, wear: Face-shield. Avoid contact with eyes.

Skin and body protection

Wear protective gloves and protective clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. None under normal use. Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapors. In confined areas, use an

approved air line respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits. Do not breathe gas/fumes/vapor/spray.

Hygiene measures

Use spark-proof tools and explosion proof equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Use only with adequate ventilation.

Canadian Province Occupational Exposure Limits

Chemical name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick - OEL	Newfoundland and Labrador - OEL	Nova Scotia - OEL	Ontario OEL	Prince Edward Island - OEL	Quebec OEL	Saskatchewan - OEL
Water	-	-	-	-	-	-	-	-	-	-
Potassium hydroxide	2 mg/m ³ Ceiling	2 mg/m ³ Ceiling	2 mg/m ³ Ceiling	2 mg/m ³ Ceiling	2 mg/m ³ Ceiling	2 mg/m ³ Ceiling	2 mg/m ³ Ceiling	2 mg/m ³ Ceiling	2 mg/m ³ Ceiling	2 mg/m ³ Ceiling
Diethylene glycol monomethyl ether	-	-	-	-	-	-	-	-	-	-
Sodium Citrate	-	-	-	-	-	-	-	-	-	-
Arsenic	0.01 mg/m ³ TWA	0.01 mg/m ³ TWA 0.01 mg/m ³ TWA	0.01 mg/m ³ TWA	0.01 mg/m ³ TWA	0.01 mg/m ³ TWA 0.01 mg/m ³ TWA	0.01 mg/m ³ TWA	0.05 mg/m ³ STEL 0.01 mg/m ³ TWA 0.01 mg/m ³ TWA 0.01 mg/m ³ TWA 0.01 mg/m ³ TWA	0.01 mg/m ³ TWA 0.01 mg/m ³ TWA	0.1 mg/m ³ TWA 0.1 mg/m ³ TWA 0.1 mg/m ³ TWA	0.03 mg/m ³ STEL 0.01 mg/m ³ TWA 0.01 mg/m ³ TWA

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid
Color	Clear, Yellow
Odor	Lemon
Odor threshold	Not available
pH	12.5 - 13.5
Melting point/range °C	Not applicable
Melting point/range °F	Not applicable
Boiling point/range °C	Not available
Boiling point/range °F	Not available
Flash point °C / °F	Not available
Evaporation rate	No data available
Flammability (Solid, Gas)	Not available
Lower explosion limit	Not available
Upper explosion limit	Not available

Vapor pressure	No data available
Vapor density	No data available
Relative density	1.073
Solubility	completely soluble in water
Partition coefficient (n-octanol/water)	Not available
Autoignition temperature °C	Not applicable
Autoignition temperature °F	Not applicable
Decomposition temperature °C	Not available
Decomposition temperature °F	Not available
Viscosity	500 cPs at 72°F

10. STABILITY AND REACTIVITY

Reactivity	No dangerous reactions under normal conditions of use.
Chemical stability	Stable at normal temperature and pressure. Avoid direct sunlight. Store at ambient or lower temperatures.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Do not allow can to exceed 120 degrees Fahrenheit. Keep away from acids. Prolonged contact with metals could produce small amounts of flammable hydrogen gas. Dilution with water creates heat. Reacts violently with organic materials.
Incompatible materials	Strong oxidizing agents. Reducing agents. Acids. organic materials.
Hazardous decomposition products	Carbon dioxide (CO2). Carbon monoxide. flammable hydrogen gas. toxic gases.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	Dermal. Eyes. Ingestion. Inhalation.
Symptoms	Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Redness.
Delayed and immediate effects as well as chronic effects from short and long-term exposure	Target Organ Effects: Eyes. Skin. Respiratory system.

Numerical measures of toxicity

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:
Water	-	-	> 90 mL/kg (Rat)
Potassium hydroxide	-	-	= 284 mg/kg (Rat)

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:
Diethylene glycol monomethyl ether	-	= 2500 µL/kg (Rabbit) = 650 mg/kg (Rabbit)	= 4 mL/kg (Rat)
Sodium Citrate	-	-	-
Arsenic	-	-	= 15 mg/kg (Rat) = 763 mg/kg (Rat)

ATEmix (dermal) Not available

ATEmix (oral) Not available

ATEmix (inhalation-gas) Not available

ATEmix (inhalation-vapor) Not available

ATEmix (inhalation-dust/mist) Not available

Carcinogenicity

Chemical name	ACGIH OEL - Carcinogens	IARC	OSHA RTK Carcinogens	NTP
Water	-	-	-	-
Potassium hydroxide	-	-	-	-
Diethylene glycol monomethyl ether	-	-	-	-
Sodium Citrate	-	-	-	-
Arsenic	A1	Group 1	Listed	Known Carcinogen

Canadian Province carcinogenicity limits

Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen
Water	-	-	-	-	-	-
Potassium hydroxide	-	-	-	-	-	-
Diethylene glycol monomethyl ether	-	-	-	-	-	-
Sodium Citrate	-	-	-	-	-	-
Arsenic	A1 - Confirmed Human Carcinogen	ACGIH A1 ACGIH A1 IARC 1 IARC 1	ACGIH A1	ACGIH A1 ACGIH A1	ACGIH A1	-

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish
Water	-	-
Potassium hydroxide	-	80: 96 h <i>Gambusia affinis</i> mg/L LC50 static
Diethylene glycol monomethyl ether	500: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	7500: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 7500: 96 h <i>Lepomis macrochirus</i> mg/L LC50 5741: 96 h <i>Pimephales promelas</i> mg/L LC50

Chemical name	Algae/aquatic plants	Fish
Sodium Citrate	-	-
Arsenic	-	-

Persistence and degradability Product is biodegradable.

Bioaccumulation No information available

Chemical name	CAS-No	Partition coefficient (log Kow)
Water 7732-18-5	7732-18-5	-
Potassium hydroxide 1310-58-3	1310-58-3	0.65 0.83
Diethylene glycol monomethyl ether 111-77-3	111-77-3	-0.682
Sodium Citrate 6132-04-03	6132-04-03	-
Arsenic 7440-38-2	7440-38-2	-

Mobility in soil This product is mobile in soil.

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Disposal information This material as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Do not dispose of waste into sewer. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Dispose of via licensed waste disposal contractor. Follow applicable NRC, CERCLA, SARA and RCRA regulations. Incinerate at a licensed waste disposal site with approved environmental authority. If this product is altered, it is the responsibility of the user to determine whether the material meets the criteria for hazardous waste at the time of disposal.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. TRANSPORTATION INFORMATION

Shipping Descriptions

DOT

ID-No UN3266
 Proper shipping name Corrosive Liquid, Basic, Inorganic, N.O.S. (Potassium Hydroxide Solution)
 Hazard Class(es) 8
 Packing group II
 Special Provisions LTD QTY: 1L or <

TDG

ID-No UN3266
 Proper shipping name Corrosive Liquid, Basic, Inorganic, N.O.S. (Potassium Hydroxide Solution)
 Hazard Class(es) 8
 Packing group II
 Special Provisions LTD QTY: 1L or <

IATA

ID-No	UN3266
Proper shipping name	Corrosive Liquid, Basic, Inorganic, N.O.S. (Potassium Hydroxide Solution)
Hazard Class(es)	8
Packing group	II
Special Provisions	LTD QTY passenger aircraft 1L, cargo aircraft only 30L

IMDG/IMO

ID-No	UN3266
Proper shipping name	Corrosive liquid, basic, inorganic, n.o.s., (Potassium Hydroxide Solution)
Hazard Class(es)	8
Packing group	II
Special Provisions	Vessel Storage Location B. LTD QTY: 1L or <

Marine Pollutants

Chemical name	CAS-No	USDOT Marine Pollutant	Canada TDG Marine Pollutant	IMDG Marine Pollutant
Water	7732-18-5	-	-	-
Potassium hydroxide	1310-58-3	-	-	-
Diethylene glycol monomethyl ether	111-77-3	-	-	-
Sodium Citrate	6132-04-03	-	-	-
Arsenic	7440-38-2	-	-	-

Special Precautions

Multi-modal shipping descriptions are provided for informational purposes and do not consider container size. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

15. REGULATORY INFORMATION

State regulations

U.S. state Right-to-Know regulations

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Water	7732-18-5	-	-	X
Potassium hydroxide	1310-58-3	X	X	X
Diethylene glycol monomethyl ether	111-77-3	X	X	X
Sodium Citrate	6132-04-03	-	-	-
Arsenic	7440-38-2	X	X	X

California Prop. 65

Chemical name	CAS-No	California Prop. 65
---------------	--------	---------------------

Chemical name	CAS-No	California Prop. 65
Water	7732-18-5	-
Potassium hydroxide	1310-58-3	-
Diethylene glycol monomethyl ether	111-77-3	-
Sodium Citrate	6132-04-03	-
Arsenic	7440-38-2	Carcinogen

U.S. Federal Regulations

US EPA SARA 313

Chemical name	CAS-No	CERCLA/SARA Hazardous Substances RQ	SARA 313 - Threshold Values
Water	7732-18-5	-	-
Potassium hydroxide	1310-58-3	1000 lb 454 kg	-
Diethylene glycol monomethyl ether	111-77-3	-	1.0 %
Sodium Citrate	6132-04-03	-	-
Arsenic	7440-38-2	1 lb 0.454 kg	0.1 %

US EPA SARA 311/312 hazardous categorization

Acute Health Hazard

Chemical name	DSL/NDSL	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification
Water	X	X	-
Potassium hydroxide	X	X	-
Diethylene glycol monomethyl ether	X	X	-
Sodium Citrate	-	-	-
Arsenic	X	X	-

Legend X - Listed

Intentionally Added Ingredient

Nonfunctional Constituents

Chemical name	CAS-No	Nonfunctional Constituents
Water	7732-18-5	Not listed
Potassium hydroxide	1310-58-3	Not listed
Diethylene glycol monomethyl ether	111-77-3	Not listed
Sodium Citrate	6132-04-03	Not listed
Arsenic	7440-38-2	Not listed

EU Fragrance Allergens

Chemical name	CAS-No	EU - Cosmetics (1223/2009) - Annex III - Fragrance Allergens
Water	7732-18-5	Not Listed
Potassium hydroxide	1310-58-3	LISTED
Diethylene glycol monomethyl ether	111-77-3	Not Listed
Sodium Citrate	6132-04-03	Not Listed
Arsenic	7440-38-2	Not Listed

California Cleaning Products RTK - Substances on Designated Lists

Chemical name	CAS-No	Substances in Designated Lists
Water	7732-18-5	Not listed
Potassium hydroxide	1310-58-3	Not listed
Diethylene glycol monomethyl ether	111-77-3	Present (CA Non-Cancer Hazards, [2292]); Present (CA Non-Cancer Hazards, [2292]); Present (applies to R-(OCH ₂ CH ₂) _n -OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or Sulfonate; US EPA PBTs, [428]); Present (including mono- and di- ethers of ethylene glycol, diethylene glycol, and triethylene glycol, except Ethylene glycol monobutyl ether [EGBE]. See 40 CFR 63.62 for Redefinition of glycol ethers listed as hazardous air pollutants and 40 CFR 63.63 for deletion of EGBE; CA TACs, [430]) Present (CA Non-Cancer Hazards, [2292]); Present (applies to R-(OCH ₂ CH ₂) _n -OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or Sulfonate; US EPA PBTs, [428]); Present (including mono- and di- ethers of ethylene glycol, diethylene glycol, and triethylene glycol, except Ethylene glycol monobutyl ether [EGBE]. See 40 CFR 63.62 for Redefinition of glycol ethers listed as hazardous air pollutants and 40 CFR 63.63 for deletion of EGBE; CA TACs, [430]) Present (CA Non-Cancer Hazards, [2292]); Present (applies to R-(OCH ₂ CH ₂) _n -OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or Sulfonate; US EPA PBTs, [428]); Present (including mono- and di- ethers of ethylene glycol, diethylene glycol, and triethylene glycol, except Ethylene glycol monobutyl ether [EGBE]. See 40 CFR 63.62 for Redefinition of glycol ethers listed as hazardous air pollutants and 40 CFR 63.63 for deletion of EGBE; CA TACs, [430])
Sodium Citrate	6132-04-03	Not listed
Arsenic	7440-38-2	Not listed

16. OTHER INFORMATION

NFPA

Health	3
Flammability	0
Instability	1
Specific hazard	Corrosive

HMIS

Health	3
Flammability	0
Physical hazards	1

Notice: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA).

Prepared by Regulatory Affairs

Issue date 13-Jul-2018

Revision date 14-Jun-2019

Revision note

Key to abbreviations

ACGIH (American Conference of Governmental Industrial Hygienists)
ATE (Average Toxicity Estimate)
DSL/NDSL (Domestic Substance List/Non-Domestic Substance List)
HMIS (Hazardous Materials Identification System)
IARC (International Agency for Research on Cancer)
IATA (International Air Transport Association)
IMDG/IMO (International Maritime Dangerous Goods/International Maritime Organization)
NFPA (National Fire Protection Association)
NTP (National Toxicology Program)
OEL (Occupational Exposure Level)
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
PEL (Permissible Exposure Limit)
TSCA (Toxic Substance Control Act)
USEPA (United States Environmental Protection Agency)

Disclaimer

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

End of Safety Data Sheet