

Issue date 09-Jul-2018

Revision date 28-Jan-2020

Revision Number 2

1. IDENTIFICATION

Product identification

Product identifier	Certanium® AWS ER5356 Aluminum TIG Wire
Other means of identification	41749
Recommended use	Brazing Alloy, Welding Alloy
Restrictions on use	For industrial use only, These items are only intended for normal welding purposes

Supplier

Corporate Headquarters:
Cronatron, A Lawson Brand
Lawson Products, Inc.
8770 W.Bryn Mawr Ave.- Suite 900
Chicago, IL 60631
1-866-529-7664

Canadian Distribution Center:
Lawson Canada
7315 Rapistan Court
Mississauga, ON L5N 5Z4
(800) 323-5922

24 Hour Emergency Phone Number (888) 426-4851 (Prosar)

Website <https://www.lawsonproducts.com>

2. HAZARD(S) IDENTIFICATION

Hazard Classification This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS 2015 and GHS Regulations.

Flammable solids	Category 2
------------------	------------

Symbol



Signal word WARNING

Hazard statements H228 - Flammable solid

Precautionary statements

Prevention P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 - Use explosion-proof electrical/ ventilating/ lighting/ equipment
 P280 - Wear protective gloves and eye/face protection

Response

Fire	P370 + P378 - IN CASE OF FIRE: Use CO2, dry chemical, or foam to extinguish
Storage	Not applicable
Disposal	Not applicable
Hazard(s) Not Otherwise Classified (HNOC)	None known.
Physical Hazards Not Otherwise Classified (PHNOC)	None known.
Unknown acute toxicity	None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition Mixture.

Chemical name	CAS-No	Weight %
Aluminum	7429-90-5	82-96
Magnesium	7439-95-4	1-10

4. FIRST-AID MEASURES

Necessary first-aid measures

Inhalation	Remove to fresh air immediately or administer oxygen. Get medical attention immediately.
Ingestion	Seek medical attention immediately.
Skin contact	Flush area with large quantities of water. Seek medical attention if irritation persists. Seek medical attention if irritation occurs.
Eye contact	Flush with plenty of water for at least 15 minutes. Get medical attention.
Most important symptoms (acute)	Electric shock can kill. For electric shock, disconnect and turn off the power. Use a nonconductive material to pull victim away from contact with live wire parts or wires. Immediately contact a physician.
Most important symptoms (over-exposure)	Not applicable.
Indication of any immediate medical attention and special treatment needed	Not applicable.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	Alcohol resistant foam. Water spray. Dry chemical. Carbon dioxide (CO2). Use the extinguishing media recommended for the burning material and fire situation.
Unsuitable extinguishing media	Water.

Specific hazards	Welding arcs and sparks can ignite combustible and flammable materials. Hazardous Thermal Decomposition Products: Aluminum oxide. Magnesium oxide.
Special protective equipment for fire-fighters	Fire fighters should wear complete protective clothing including self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Use personal protection recommended in Section 8. For waste disposal, see section 13 of the SDS.
Methods and materials for containment and cleaning up	Solid objects may be picked up and placed in a container. Make sure the solid objects are at room temperature before handling. Liquids or pastes should be scooped up and placed into a container. Wear proper protective equipment while handling these materials. Do not discard as refuse.

7. HANDLING AND STORAGE

Precautions for safe handling	Handle with care to avoid stings or cuts. Wear gloves when handling welding consumables. Avoid exposure to dust and do not ingest. Some individuals may develop an allergic reaction to certain materials. Retain all warning and identity labels.
Conditions for safe storage, including any incompatibilities	Store in a cool, dry, and well-ventilated place. Keep container tightly closed. Keep away from water.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical name	OSHA PEL (TWA)	ACGIH OEL (TWA)	NIOSH - TWA
Aluminum	15 mg/m ³ TWA 5 mg/m ³ TWA	1 mg/m ³ TWA	10 mg/m ³ TWA 5 mg/m ³ TWA 5 mg/m ³ TWA 5 mg/m ³ TWA
Magnesium	-	-	-

Appropriate engineering controls	Avoid exposure to welding fumes, radiation, spatter, electric shock, heated materials and dust. Ensure sufficient ventilation, local exhaust, or both, to keep welding fumes and gases from breathing zone and general area. Keep workplace and protective clothing clean and dry. Train the welder not to touch live electrical parts and to insulate himself from work and ground. Check condition of protective clothing and equipment on a regular basis. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Processing may form hazardous compounds, refer to section 10.
---	---

Individual protection measures, such as personal protective equipment

Eye protection	Welder's helmet or face shield with color absorbing lenses. Shield and filter to provide protection from harmful UV radiation, infrared and molten metal approved to standard EN379. Filter shade to be a minimum of shade 9.
Skin and body protection	Heat-resistant protective clothing. Wear safety boots, apron, arm and shoulder protection. Keep protective clothing clean and dry. Clothing should be selected to suit the level, duration and purpose of the welding activity. Wear appropriate gloves to prevent skin contact. Wear welding gloves.
Respiratory protection	Use an air purifying dust respirator when welding or brazing in a confined space, or when local exhaust or ventilation is not sufficient to keep exposure values within safe limits.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

Canadian Province Occupational Exposure Limits

Chemical name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick - OEL	Newfoundland and Labrador - OEL	Nova Scotia - OEL	Ontario OEL	Prince Edward Island - OEL	Quebec OEL	Saskatchewan - OEL
Aluminum	10 mg/m ³ TWA 5 mg/m ³ TWA	1.0 mg/m ³ TWA	1 mg/m ³ TWA	10 mg/m ³ TWA 5 mg/m ³ TWA	1 mg/m ³ TWA	1 mg/m ³ TWA	1 mg/m ³ TWA	1 mg/m ³ TWA	10 mg/m ³ TWA TWA EV 5 mg/m ³ TWA EV 5 mg/m ³ TWA EV	10 mg/m ³ TWA 5 mg/m ³ TWA
Magnesium	-	-	-	-	-	-	-	-	-	-

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Solid
Color	Metallic
Odor	Odorless
Odor threshold	Not applicable
pH	Not applicable
Melting point/range °C	565-593 °C
Melting point/range °F	1050-1100 °F
Boiling point/range °C	Not available
Boiling point/range °F	Not available
Flash point °C / °F	Not applicable
Evaporation rate	Not applicable
Flammability (Solid, Gas)	Not available
Lower explosion limit	Not applicable
Upper explosion limit	Not applicable
Vapor pressure	Not applicable
Vapor density	Not applicable
Relative density	6
Solubility	Insoluble in water
Partition coefficient (n-octanol/water)	Not applicable
Autoignition temperature °C	Not applicable

Autoignition temperature °F	Not applicable
Decomposition temperature °C	Not available
Decomposition temperature °F	Not available
Viscosity	Not available

10. STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	Contact with chemical substances like acids or strong bases could cause generation of gas. Keep away from any possible contact with water, because of violent reaction and possible flash fire.
Conditions to avoid	Stable under normal conditions.
Incompatible materials	Incompatible with acids. Avoid contact with moisture and water.
Hazardous decomposition products	When this product is used in a welding process, hazardous decomposition products would include those from volatilization, reaction or oxidation of the materials listed in section 3 and those from the base metal and coating. The amount of fumes generated from this product varies with welding parameters and dimensions. Refer to applicable national exposure limits for the fume compounds. Reasonably expected gaseous products would include: carbon oxides. Nitrogen oxides (NOx). Ozone. Air contaminants around the welding area can be affected by the welding process and influence the composition and quality of fumes and gases produced.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	Dermal. Inhalation.
Symptoms	Prolonged inhalation may be harmful. Welding fumes cannot be classified simply. Their composition and quantity are dependent upon the metal being welded, the process, procedures and electrodes being used. Overexposure to welding fumes may result in discomfort such as metal fume fever, dizziness, nausea, or dryness or irritation of nose, throat or eyes. May cause sensitization by skin contact.
Delayed and immediate effects as well as chronic effects from short and long-term exposure	Overexposure to welding fumes may affect pulmonary function and eyes.

Numerical measures of toxicity

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:
Aluminum	-	-	-
Magnesium	-	-	= 230 mg/kg (Rat)

ATEmix (dermal)	Not available
ATEmix (oral)	Not available
ATEmix (inhalation-gas)	Not available
ATEmix (inhalation-vapor)	Not available

ATEmix (inhalation-dust/mist) Not available

Carcinogenicity

Chemical name	ACGIH OEL - Carcinogens	IARC	OSHA Carcinogens	NTP
Aluminum	A4	-	-	-
Magnesium	-	-	-	-

Canadian Province carcinogenicity limits

Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen
Aluminum	-	-	ACGIH A4	-	ACGIH A4	-
Magnesium	-	-	-	-	-	-

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish
Aluminum	-	-
Magnesium	-	-

Persistence and degradability Not readily biodegradable.

Bioaccumulation

Chemical name	CAS-No	Partition coefficient (log Kow)
Aluminum 7429-90-5	7429-90-5	-
Magnesium 7439-95-4	7439-95-4	-

Mobility in soil This product is not mobile in the soil.

Other adverse effects Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

13. DISPOSAL CONSIDERATIONS

Disposal information As supplied, this product is a RCRA Hazardous Waste. Discard container or liner in accordance with federal, state, and local regulations.

Contaminated packaging Dispose in accordance with local, state and federal regulations.

14. TRANSPORTATION INFORMATION

Shipping Descriptions

DOT

Proper shipping name Not regulated

TDG

Proper shipping name Not regulated

IATA

Proper shipping name Not regulated

IMDG/IMO

Proper shipping name Not regulated

Marine Pollutants

Chemical name	CAS-No	USDOT Marine Pollutant	Canada TDG Marine Pollutant	IMDG Marine Pollutant
Aluminum	7429-90-5	-	-	-
Magnesium	7439-95-4	-	-	-

Special Precautions

Multi-modal shipping descriptions are provided for informational purposes and do not consider container size. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

15. REGULATORY INFORMATION**State regulations****U.S. state Right-to-Know regulations**

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Aluminum	7429-90-5	X	X	X
Magnesium	7439-95-4	X	X	X

California Prop. 65

Chemical name	CAS-No	California Prop. 65
Aluminum	7429-90-5	-
Magnesium	7439-95-4	-

U.S. Federal Regulations**US EPA SARA 313**

Chemical name	CAS-No	CERCLA/SARA Hazardous Substances RQ	SARA 313 - Threshold Values
Aluminum	7429-90-5	-	1.0 %
Magnesium	7439-95-4	-	-

**US EPA SARA 311/312
hazardous categorization**

Not applicable

Chemical name	DSL/NDSL	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification
Aluminum	X	X	-
Magnesium	X	X	-

Legend X - Listed

16. OTHER INFORMATION

NFPA

Health	Not available
Flammability	Not available
Instability	Not available

HMIS

Health	Not available
Flammability	Not available
Physical hazards	Not available

Notice: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA).

Prepared by Regulatory Affairs

Issue date 09-Jul-2018

Revision date 28-Jan-2020

Revision note

Key to abbreviations

ACGIH (American Conference of Governmental Industrial Hygienists)
 ATE (Average Toxicity Estimate)
 DSL/NDSL (Domestic Substance List/Non-Domestic Substance List)
 HMIS (Hazardous Materials Identification System)
 IARC (International Agency for Research on Cancer)
 IATA (International Air Transport Association)
 IMDG/IMO (International Maritime Dangerous Goods/International Maritime Organization)
 NFPA (National Fire Protection Association)
 NTP (National Toxicology Program)
 OEL (Occupational Exposure Level)
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 PEL (Permissible Exposure Limit)
 TSCA (Toxic Substance Control Act)

USEPA (United States Environmental Protection Agency)

Disclaimer

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

End of Safety Data Sheet