Safety Data Sheet

Issue date 26-Sep-2018 **Revision date** 16-Jan-2020 **Revision Number** 2

1. IDENTIFICATION

Product identification

Product identifier	Regency® Wire Wheel
Other means of identification	89196
Recommended use	Abrasive
Restrictions on use	For industrial use only, Restricted to professional users

Supplier

Corporate Headquarters:
Lawson Products, Inc.
8770 W. Bryn Mawr Ave., Suite 900
Chicago, IL 60631
(866) 837-9908

Canadian Distribution Center:
Lawson Canada
7315 Rapistan Court
Mississauga, ON L5N 5Z4
(800) 323-5922

24 Hour Emergency Phone Number (888) 426-4851 (Prosar)

Website https://www.lawsonproducts.com

Methylene Chloride notification No Information Available

2. HAZARD(S) IDENTIFICATION

Hazard Classification While this material is not classified as hazardous under OSHA, GHS or WHMIS 2015 regulations, this SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

Symbol Not applicable

Signal word Not applicable

Hazard statements Not applicable

Precautionary statements

Response Not applicable

Storage Not applicable

Disposal Not applicable

Hazard(s) Not Otherwise Not applicable.

Classified (HNOC)

Physical Hazards Not Otherwise Classified (PHNOC) Not applicable.

Unknown acute toxicity None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition This product is classified as an "article" according to Title 29 of the Code of Federal Regulations, OSHA Part 1910.1200. "Article means a manufactured item other than a fluid or particle, which is formed to a specific shape or design during manufacture which has end use function dependent in whole or in part upon its shape or design during end use, and which under normal conditions of use does not release more than very small quantities or trace amounts of a hazardous chemical, and does not pose a physical hazard or health risk to employees.".

Chemical name	CAS-No	Weight %
Iron	7439-89-6	95-99
Manganese	7439-96-5	0.25-1.65
Silicon	7440-21-3	<1.6
Carbon	7440-44-0	0.01-1.1
Chromium	7440-47-3	0.01-1.5
Vanadium	7440-62-2	0-0.35
Phosphorus	7723-14-0	<0.04
Sulfur	7704-34-9	0-0.035
Lead	7439-92-1	0-0.005

4. FIRST-AID MEASURES

Necessary first-aid measures

General Information For further assistance, contact your local Poison Control Center.

Inhalation Remove to fresh air. If breathing is difficult, give oxygen. Seek medical attention.

Ingestion Seek medical attention.

Skin contact Wash area thoroughly with soap and water. Seek medical attention if irritation occurs.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

Most important symptoms (acute) Excessive inhalation of fumes may cause 'Metal Fume Fever' with flu-like symptoms such as chills, fever, body aches, vomiting, sweating, etc. Symptoms may be delayed. May cause eye irritation. May cause skin irritation.

Most important symptoms (over-exposure) None known.

Indication of any immediate medical attention and special treatment needed Not applicable.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media Not available.

Specific hazards None known.

Special protective equipment for fire-fighters In the event of fire, wear self-contained breathing apparatus and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Wear appropriate protective equipment and clothing during cleanup.

Methods and materials for containment and cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling Avoid contact with eyes, skin, and clothing.

Conditions for safe storage, including any incompatibilities No special storage conditions required.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical name	OSHA PEL (TWA)	ACGIH OEL (TWA)	NIOSH - TWA
Iron	-	-	-
Manganese	5 mg/m³ Ceiling	0.02 mg/m³ TWA 0.1 mg/m³ TWA	3 mg/m³ STEL 1 mg/m³ TWA 1 mg/m³ TWA
Silicon	15 mg/m³ TWA 5 mg/m³ TWA	-	10 mg/m³ TWA 5 mg/m³ TWA
Carbon	-	-	-
Chromium	1 mg/m³ TWA	0.5 mg/m³ TWA	0.5 mg/m³ TWA
Vanadium	0.5 mg/m³ Ceiling 0.1 mg/m³ Ceiling	-	3 mg/m³ STEL 1 mg/m³ TWA
Phosphorus	-	-	-
Sulfur	-	-	-
Lead	50 µg/m³ TWA 50 µg/m³ TWA	0.05 mg/m³ TWA	0.050 mg/m³ TWA 0.050 mg/m³ TWA

Appropriate engineering controls Adequate ventilation should be provided to keep exposure levels below current acceptable exposure limits. Consider potential exposure to components of the base materials or coatings being ground or cut.

Individual protection measures, such as personal protective equipment

Eye protection ANSI approved safety glasses or splash goggles with face shield are recommended.

Hearing Protection Use hearing protection if operations are noisy.

Skin and body protection Wear suitable protective clothing. Leather gloves.

Respiratory protection Use a properly fitted, particulate filter respirator complying with an approved standard if a

risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Consider potential exposure to components of the base materials or coatings being ground or cut. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures Handle in accordance with good industrial hygiene and safety practice.

Canadian Province Occupational Exposure Limits

Chemical name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick - OEL	Newfoundland & Labrador - OEL	Nova Scotia - OEL	Ontario OEL	Prince Edward Island - OEL	Quebec OEL	Saskatchewan - OEL
Iron	-	-	-	-	-	-	-	-	-	-
Manganese	0.2 mg/m³ TWA	0.2mg/m³TWA 0.02mg/m³	0.02 mg/m³ TWA 0.1 mg/m³ TWA	0.2 mg/m³ TWA	0.02 mg/m³ TWA 0.1 mg/m³ TWA 0.02 mg/m³ TWA 0.1 mg/m³ TWA	0.02 mg/m³ TWA 0.1 mg/m³ TWA	0.2 mg/m³ TWA 0.02 mg/m³ TWA 0.1 mg/m³ TWA	0.02 mg/m³ TWA 0.1 mg/m³ TWA 0.02 mg/m³ TWA 0.1 mg/m³ TWA	0.2 mg/m³ TWAEV 0.2 mg/m³ TWAEV	0.6 mg/m³ STEL 0.2 mg/m³ TWA 0.2 mg/m³ TWA
Silicon	-	10mg/m³TWA 3mg/m³TWA	-	10 mg/m³ TWA	-	-	-	-	10 mg/m³ TWAEV	20 mg/m³ STEL 10 mg/m³ TWA
Carbon	-	-	-	-	-	-	-	-	-	-
Chromium	0.5 mg/m³ TWA	0.5mg/m³TWA	0.5 mg/m³ TWA	0.5 mg/m³ TWA	0.5 mg/m³ TWA	0.5 mg/m³ TWA	0.5 mg/m³ TWA	0.5 mg/m³ TWA	0.5 mg/m³ TWAEV	1.5 mg/m³ STEL 0.5 mg/m³ TWA
Vanadium	-	-	-	-	-	-	-	-	-	-
Phosphorus	0.1 mg/m³ TWA	-	-	0.02 ppm TWA 0.1 mg/m³ TWA	-	-	-	-	0.1 mg/m³ TWAEV	-
Sulfur	10 mg/m³ TWA	-	-	-	-	-	-	-	-	-
Lead	0.05 mg/m³ TWA	0.05mg/m³TWA	0.05 mg/m³ TWA	0.05 mg/m³ TWA	0.05 mg/m³ TWA 0.05 mg/m³ TWA	0.05 mg/m³ TWA	0.05 mg/m³ TWA 0.05 mg/m³ TWA 0.05 mg/m³ TWA 0.05 mg/m³ TWA	0.05 mg/m³ TWA 0.05 mg/m³ TWA	0.05 mg/m³ TWAEV 0.05 mg/m³ TWAEV	0.15 mg/m³ STEL 0.05 mg/m³ TWA 0.05 mg/m³ TWA

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state Solid

Color Gray

Odor Odorless

Odor threshold Not available

pH Not available

Melting point/range °C Not available

Melting point/range °F Not available

Boiling point/range °C Not available

Boiling point/range °F	Not available
Flash point °C / °F	Not available
Evaporation rate	Not available
Flammability (Solid, Gas)	Not available
Lower explosion limit	Not available
Upper explosion limit	Not available
Vapor pressure	Not available
Vapor density	Not available
Relative density	7
Solubility	insoluble
Partition coefficient (n-octanol/water)	Not available
Autoignition temperature °C	Not available
Autoignition temperature °F	Not available
Decomposition temperature °C	Not available
Decomposition temperature °F	Not available
Viscosity	Not available

10. STABILITY AND REACTIVITY

Reactivity	Not available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal conditions of use.
Conditions to avoid	None known.
Incompatible materials	None known.
Hazardous decomposition products	Hazardous Thermal Decomposition Products:. Hazardous metal fumes and oxides. Iron oxide fume. Manganese. Chromium. Molybdenum. vanadium.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	Product does not present an acute toxicity hazard based on known information.
Symptoms	Not classified.
Delayed and immediate effects as well as chronic effects from short and long-term exposure	Not classified.

Numerical measures of toxicity

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:
Iron	-	-	= 30 g/kg (Rat)
Manganese	-	-	= 9 g/kg (Rat)
Silicon	-	-	= 3160 mg/kg (Rat)
Carbon	-	-	> 10000 mg/kg (Rat)
Chromium	-	-	-
Vanadium	-	-	> 2000 mg/kg (Rat)
Phosphorus	= 4.3 mg/L (Rat) 1 h	= 100 mg/kg (Rat)	= 3030 µg/kg (Rat)
Sulfur	> 9.23 mg/L (Rat) 4 h	> 2000 mg/kg (Rabbit)	> 3000 mg/kg (Rat)
Lead	-	-	-

ATEmix (dermal) Not available

ATEmix (oral) Not available

ATEmix (inhalation-gas) Not available

ATEmix (inhalation-vapor) Not available

ATEmix (inhalation-dust/mist) Not available

Carcinogenicity

Chemical name	ACGIH OEL - Carcinogens	IARC	OSHA RTK Carcinogens	NTP
Iron	-	-	-	-
Manganese	A4	-	-	-
Silicon	-	-	-	-
Carbon	-	-	-	-
Chromium	A4	Group 3	-	-
Vanadium	-	-	-	-
Phosphorus	-	-	-	-
Sulfur	-	-	-	-
Lead	A3	Group 2A	Listed	Reasonably Anticipated Carcinogen

Canadian Province carcinogenicity limits

Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen
Iron	-	-	-	-	-	-
Manganese	-	-	ACGIH A4	-	ACGIH A4	-
Silicon	-	-	-	-	-	-
Carbon	-	-	-	-	-	-
Chromium	-	-	ACGIH A4	ACGIH A4	ACGIH A4	-
Vanadium	-	-	-	-	-	-
Phosphorus	-	-	-	-	-	-
Sulfur	-	-	-	-	-	-
Lead	-	IARC 2A IARC 2B	ACGIH A3	ACGIH A3	ACGIH A3	C3 carcinogen

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish
Iron	-	13.6: 96 h Morone saxatilis mg/L LC50 static
Manganese	-	-
Silicon	-	-
Carbon	-	-
Chromium	-	-
Vanadium	-	-
Phosphorus	-	0.0017 - 0.0035: 96 h Lepomis macrochirus mg/L LC50 flow-through 0.001 - 0.004: 96 h Lepomis macrochirus mg/L LC50 static 100: 96 h Brachydanio rerio mg/L LC50 static 0.015 - 0.032: 96 h Oncorhynchus mykiss mg/L LC50 static 0.011 - 0.028: 96 h Pimephales promelas mg/L LC50 static
Sulfur	-	866: 96 h Brachydanio rerio mg/L LC50 static 14: 96 h Lepomis macrochirus mg/L LC50 static 180: 96 h Oncorhynchus mykiss mg/L LC50 static
Lead	-	0.44: 96 h Cyprinus carpio mg/L LC50 semi-static 1.17: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 1.32: 96 h Oncorhynchus mykiss mg/L LC50 static

Persistence and degradability No data available.

Bioaccumulation

Chemical name	CAS-No	Partition coefficient (log Kow)
Iron 7439-89-6	7439-89-6	-
Manganese 7439-96-5	7439-96-5	-
Silicon 7440-21-3	7440-21-3	-
Carbon 7440-44-0	7440-44-0	-
Chromium 7440-47-3	7440-47-3	-
Vanadium 7440-62-2	7440-62-2	-
Phosphorus 7723-14-0	7723-14-0	-
Sulfur 7704-34-9	7704-34-9	-
Lead 7439-92-1	7439-92-1	-

Mobility in soil Not available.

Other adverse effects None known

13. DISPOSAL CONSIDERATIONS

Disposal information Collect, transport, store or dispose in accordance with local, state, provincial and federal regulations.

Contaminated packaging Dispose in accordance with local, state and federal regulations.

14. TRANSPORTATION INFORMATION

Shipping Descriptions

DOT
Proper shipping name Not regulated

TDG
Proper shipping name Not regulated

IATA
Proper shipping name Not regulated

IMDG/IMO
Proper shipping name Not regulated

Marine Pollutants

Chemical name	CAS-No	USDOT Marine Pollutant	Canada TDG Marine Pollutant	IMDG Marine Pollutant
Iron	7439-89-6	-	-	-
Manganese	7439-96-5	-	-	-
Silicon	7440-21-3	-	-	-
Carbon	7440-44-0	-	-	-
Chromium	7440-47-3	-	-	-
Vanadium	7440-62-2	-	-	-
Phosphorus	7723-14-0	-	-	-
Sulfur	7704-34-9	-	-	-
Lead	7439-92-1	-	-	-

Special Precautions Multi-modal shipping descriptions are provided for informational purposes and do not consider container size. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

15. REGULATORY INFORMATION

State regulations

U.S. state Right-to-Know regulations

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Iron	7439-89-6	-	-	-
Manganese	7439-96-5	X	X	X
Silicon	7440-21-3	X	X	X
Carbon	7440-44-0	-	-	-
Chromium	7440-47-3	X	X	X
Vanadium	7440-62-2	X	X	X

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Phosphorus	7723-14-0	X	X	X
Sulfur	7704-34-9	X	X	X
Lead	7439-92-1	X	X	X

California Prop. 65 WARNING: This product contains a chemical(s) known to the state of California to cause cancer, birth defects or other reproductive harm

Chemical name	CAS-No	California Prop. 65
Iron	7439-89-6	-
Manganese	7439-96-5	-
Silicon	7440-21-3	-
Carbon	7440-44-0	-
Chromium	7440-47-3	-
Vanadium	7440-62-2	-
Phosphorus	7723-14-0	-
Sulfur	7704-34-9	-
Lead	7439-92-1	Carcinogen Developmental Female Reproductive Male Reproductive

U.S. Federal Regulations

Methylene Chloride notification No Information Available

US EPA SARA 313

Chemical name	CAS-No	CERCLA/SARA Hazardous Substances RQ	SARA 313 - Threshold Values
Iron	7439-89-6	-	-
Manganese	7439-96-5	-	1.0 %
Silicon	7440-21-3	-	-
Carbon	7440-44-0	-	-
Chromium	7440-47-3	5000 lb 2270 kg 10 lb 4.54 kg	1.0 %
Vanadium	7440-62-2	-	1.0 %
Phosphorus	7723-14-0	1 lb 0.454 kg	1.0 %
Sulfur	7704-34-9	-	-
Lead	7439-92-1	10 lb 4.54 kg	0.1 %

US EPA SARA 311/312 hazardous categorization Not applicable

Chemical name	DSL/NDSL	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification
Iron	X	X	-
Manganese	X	X	-
Silicon	X	X	-

Chemical name	DSL/NDSL	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification
Carbon	X	X	-
Chromium	X	X	-
Vanadium	X	X	-
Phosphorus	X	X	-
Sulfur	X	X	-
Lead	X	X	-

Legend X - Listed

16. OTHER INFORMATION

NFPA

Health Not available
Flammability Not available
Instability Not available

HMIS

Health Not available
Flammability Not available
Physical hazards Not available

Notice: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA).

Prepared by Regulatory Affairs

Issue date 26-Sep-2018

Revision date 16-Jan-2020

Revision note

Key to abbreviations

ACGIH (American Conference of Governmental Industrial Hygienists)
ATE (Average Toxicity Estimate)
DSL/NDSL (Domestic Substance List/Non-Domestic Substance List)
HMIS (Hazardous Materials Identification System)
IARC (International Agency for Research on Cancer)
IATA (International Air Transport Association)
IMDG/IMO (International Maritime Dangerous Goods/International Maritime Orgnaization)
NFPA (National Fire Protection Association)
NTP (National Toxicology Program)
OEL (Occupational Exposure Level)
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
PEL (Permissible Exposure Limit)
TSCA (Toxic Substance Control Act)
USEPA (United States Environmental Protection Agency)

Disclaimer

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

End of Safety Data Sheet