

Issue date 05-Apr-2019

Revision date 05-Apr-2019

Revision Number 1

1. IDENTIFICATION

Product identification

Product identifier	Kent® Plastic Quick Fix Plastic Repair - Part B
Other means of identification	KT13139B
Recommended use	Sealant
Restrictions on use	For industrial use only

Supplier

Corporate Headquarters:
Kent Automotive
8770 W. Bryn Mawr Ave.- Suite 900
Chicago, IL 60631
(888)-937-5368

Canadian Distribution Center:
Lawson Canada
7315 Rapistan Court
Mississauga, ON L5N 5Z4
(800) 323-5922

24 Hour Emergency Phone Number (888) 426-4851 (Prosar)

Website <https://www.lawsonproducts.com>

2. HAZARD(S) IDENTIFICATION

Hazard Classification This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Specific target organ toxicity (single exposure)	Category 2

Symbol



Signal word WARNING

Hazard statements H371 - May cause damage to organs

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H302 - Harmful if swallowed

Precautionary statements

Prevention

P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P264 - Wash skin thoroughly after handling
P272 - Contaminated work clothing should not be allowed out of the workplace
P270 - Do not eat, drink or smoke when using this product
P280 - Wear protective gloves and eye/face protection

Response

General

P321 - For Specific treatment see section 4 of this sds
P308 + P313 - IF exposed or concerned: Get medical advice/attention

Eyes

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337 + P313 - If eye irritation persists: Get medical advice/attention

Skin

P302 + P352 - IF ON SKIN: Wash with plenty of water.
P362 - Take off contaminated clothing and wash before reuse
P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention
P363 - Wash contaminated clothing before reuse

Ingestion

P301 + P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
P330 - Rinse mouth

Storage

P405 - Store locked up

Disposal

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Hazard(s) Not Otherwise Classified (HNOC)

Not applicable.

Physical Hazards Not Otherwise Classified (PHNOC)

Not applicable.

Unknown acute toxicity

Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition

Mixture.

Chemical name	CAS-No	Weight %
Bisphenol A - Epichlorohydrin polymer	25068-38-6	40-60
Epoxy Resin Blend	Mixture	13-30
Modified Silicone Dioxide	67762-90-7	1.5-5
Elastomer Modified Diglycidyl Ether	163440-98-0	1.5-5
Cyclohexanedimethanol Diglycidyl Ether	14228-73-0	1.5-5
Glycidoxypentyl-Trimethoxysilane	2530-83-8	1-1.5
Water, distilled, conductivity or of similar purity	7732-18-5	<1

Quartz (Crystalline Silica)	14808-60-7	<1
Methanol	67-56-1	<1
Ethylene glycol	107-21-1	<1
Carbon Black	1333-86-4	<1
Calcium Carbonate	1317-65-3	<1

4. FIRST-AID MEASURES

Necessary first-aid measures

General Information	Immediately remove all soiled and contaminated clothing. Symptoms of poisoning may occur, even after several hours. Keep under medical supervision for at least 48 hours.
Inhalation	Remove to fresh air. If unconscious, place patient in side position for transportation. Seek medical attention.
Ingestion	Call a physician immediately.
Skin contact	Wash off immediately with soap and plenty of water.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.

Most important symptoms (acute) No further relevant information available.

Most important symptoms (over-exposure) No known significant effects or critical hazards.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	Carbon dioxide (CO ₂). Extinguishing powder. Water spray. Fight larger fires with water spray or alcohol resistant foam.
Unsuitable extinguishing media	None known.
Specific hazards	In use, may form flammable/explosive vapour-air mixture.
Special protective equipment for fire-fighters	No special measures are required.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Do not allow product to reach sewage system, soil, surface or ground water, or any water course. Notify proper authorities if entry occurs.
Methods and materials for containment and cleaning up	Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Clean up residue with soap and water. Dispose of absorbent in accordance with local, state and federal regulations. Ensure adequate ventilation.

7. HANDLING AND STORAGE

Precautions for safe handling

No special handling procedures needed. Use only with adequate ventilation. Open and handle receptacle with care.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical name	OSHA PEL (TWA)	ACGIH OEL (TWA)	NIOSH - TWA
Bisphenol A - Epichlorohydrin polymer	-	-	-
Epoxy Resin Blend	-	-	-
Modified Silicone Dioxide	-	-	-
Elastomer Modified Diglycidal Ether	-	-	-
Cyclohexanedimethanol Diglycidyl Ether	-	-	-
Glycidoxypopyl-Trimethoxysilane	-	-	-
Water, distilled, conductivity or of similar purity	-	-	-
Quartz (Crystalline Silica)	50 µg/m³ TWA 50 µg/m³ TWA	0.025 mg/m³ TWA	0.05 mg/m³ TWA
Methanol	200 ppm TWA 260 mg/m³ TWA	250 ppm STEL 200 ppm TWA Skin	250 ppm STEL 325 mg/m³ STEL 200 ppm TWA 260 mg/m³ TWA
Ethylene glycol	-	50 ppm STEL 10 mg/m³ STEL 25 ppm TWA	-
Carbon Black	3.5 mg/m³ TWA	3 mg/m³ TWA	3.5 mg/m³ TWA 0.1 mg/m³ TWA
Calcium Carbonate	15 mg/m³ TWA 5 mg/m³ TWA	-	10 mg/m³ TWA 5 mg/m³ TWA

Appropriate engineering controls

Ensure adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye protection

Tightly fitting safety goggles.

Skin and body protection

Chemical-resistant, impervious gloves (Nitrile or Viton) complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use the the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Respiratory protection

None under normal use. Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapors. In confined areas, use an approved air line respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Hygiene measures

Keep away from food, drink and animal feeding stuffs. Remove and wash contaminated clothing before re-use. Wash hands before breaks and at the end of workday. Avoid contact with skin, eyes and clothing. Store protective clothing separately.

**Canadian Province Occupational
Exposure Limits**

Chemical name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick - OEL	Newfoundl and & Labrador - OEL	Nova Scotia - OEL	Ontario OEL	Prince Edward Island - OEL	Quebec OEL	Saskatche wan - OEL
Bisphenol A - Epichlorohydrin polymer	-	-	-	-	-	-	-	-	-	-
Epoxy Resin Blend	-	-	-	-	-	-	-	-	-	-
Modified Silicone Dioxide	-	-	-	-	-	-	-	-	-	-
Elastomer Modified Diglycidial Ether	-	-	-	-	-	-	-	-	-	-
Cyclohexanedimeth anol Diglycidyl Ether	-	-	-	-	-	-	-	-	-	-
Glycidoxypyrrol-Tri methoxysilane	-	-	-	-	-	-	-	-	-	-
Water, distilled, conductivity or of similar purity	-	-	-	-	-	-	-	-	-	-
Quartz (Crystalline Silica)	0.025 mg/m ³ TWA	0.025 mg/m ³ TWA	0.025 mg/m ³ TWA	0.1 mg/m ³ TWA	0.025 mg/m ³ TWA	0.025 mg/m ³ TWA	0.10 mg/m ³ TWA	0.025 mg/m ³ TWA	0.1 mg/m ³ TWA	0.05 mg/m ³ TWA
Methanol	250 ppm STEL 328 mg/m ³ STEL 200 ppm TWA 262 mg/m ³ TWA	250 ppm STEL 200 ppm TWA	200 ppm TWA 250 ppm STEL	250 ppm STEL 328 mg/m ³ STEL 200 ppm TWA 262 mg/m ³ TWA	250 ppm STEL 200 ppm TWA	250 ppm STEL 200 ppm TWA	250 ppm STEL 200 ppm TWA	250 ppm STEL 200 ppm TWA	250 ppm STEL 328 mg/m ³ STEL 200 ppm TWA 262 mg/m ³ TWA	250 ppm STEL 200 ppm TWA
Ethylene glycol	100 mg/m ³ Ceiling	100 mg/m ³ Ceiling 50 ppm Ceiling 20 mg/m ³ STEL 10 mg/m ³ TWA	25 ppm TWA 50 ppm STEL 10 mg/m ³ STEL	100 mg/m ³ Ceiling	50 ppm STEL 10 mg/m ³ STEL 25 ppm TWA	50 ppm STEL 10 mg/m ³ STEL 25 ppm TWA	100 mg/m ³ Ceiling	50 ppm STEL 10 mg/m ³ STEL 25 ppm TWA	50 ppm Ceiling 127 mg/m ³ Ceiling	100 mg/m ³ Ceiling
Carbon Black	3.5 mg/m ³ TWA	3 mg/m ³ TWA	3 mg/m ³ TWA	3.5 mg/m ³ TWA	3 mg/m ³ TWA	3 mg/m ³ TWA	3 mg/m ³ TWA	3 mg/m ³ TWA	3.5 mg/m ³ TWA	7 mg/m ³ STEL 3.5 mg/m ³ TWA
Calcium Carbonate	10 mg/m ³ TWA	20 mg/m ³ STEL 10 mg/m ³ TWA 3 mg/m ³ TWA	-	10 mg/m ³ TWA	-	-	-	-	10 mg/m ³ TWA	20 mg/m ³ STEL 10 mg/m ³ TWA

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid
Color	Black
Odor	Characteristic
Odor threshold	No information available
pH	No data available

Melting point/range °C	No data available
Melting point/range °F	No data available
Boiling point/range °C	>260 °C
Boiling point/range °F	>500 °F
Flash point °C	94
Flash point °F	201.2
Flash point method used	Not available
Evaporation rate	No data available
Flammability (Solid, Gas)	No data available
Lower explosion limit	Not available
Upper explosion limit	Not available
Vapor pressure	No data available
Vapor density	No data available
Relative density	1.2685
Solubility	Insoluble in water
Partition coefficient (n-octanol/water)	No data available
Autoignition temperature °C	Not available
Autoignition temperature °F	No data available
Decomposition temperature °C	No data available
Decomposition temperature °F	No data available
Viscosity	No data available

10. STABILITY AND REACTIVITY

Reactivity	Not available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None known.
Conditions to avoid	None known.
Incompatible materials	No further relevant information available.
Hazardous decomposition products	None known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Dermal. Eyes. Inhalation.

Symptoms

Causes irritation to the mucous membranes. Skin irritation. Eye irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization possible through skin contact.

Numerical measures of toxicity

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:
Bisphenol A - Epichlorohydrin polymer	-	-	= 11400 mg/kg (Rat)
Epoxy Resin Blend	-	-	-
Modified Silicone Dioxide	-	-	-
Elastomer Modified Diglycidyl Ether	-	-	-
Cyclohexanedimethanol Diglycidyl Ether	-	-	-
Glycidoxypopyl-Trimethoxysilane	> 5.3 mg/L (Rat) 4 h	= 3970 µL/kg (Rabbit)	= 22600 µL/kg (Rat) = 7.01 g/kg (Rat)
Water, distilled, conductivity or of similar purity	-	-	> 90 mL/kg (Rat)
Quartz (Crystalline Silica)	-	-	-
Methanol	= 22500 ppm (Rat) 8 h = 64000 ppm (Rat) 4 h	= 15800 mg/kg (Rabbit) = 15840 mg/kg (Rabbit)	= 6200 mg/kg (Rat)
Ethylene glycol	-	= 10600 mg/kg (Rat) = 9530 µL/kg (Rabbit)	= 4700 mg/kg (Rat)
Carbon Black	-	> 3 g/kg (Rabbit)	> 15400 mg/kg (Rat)
Calcium Carbonate	-	-	-

ATEmix (dermal)

Not available

ATEmix (oral)

Not available

ATEmix (inhalation-gas)

Not available

ATEmix (inhalation-vapor)

Not available

ATEmix (inhalation-dust/mist)

Not available

Carcinogenicity

Chemical name	ACGIH OEL - Carcinogens	IARC	OSHA RTK Carcinogens	NTP
Bisphenol A - Epichlorohydrin polymer	-	-	-	-
Epoxy Resin Blend	-	-	-	-
Modified Silicone Dioxide	-	-	-	-
Elastomer Modified Diglycidyl Ether	-	-	-	-
Cyclohexanedimethanol Diglycidyl Ether	-	-	-	-
Glycidoxypopyl-Trimethoxysilane	-	-	-	-
Water, distilled, conductivity or of similar purity	-	-	-	-

Chemical name	ACGIH OEL - Carcinogens	IARC	OSHA RTK Carcinogens	NTP
Quartz (Crystalline Silica)	A2	Group 1	Listed	Known Carcinogen
Methanol	-	-	-	-
Ethylene glycol	A4	-	-	-
Carbon Black	A3	Group 2B	Listed	-
Calcium Carbonate	-	-	-	-

**Canadian Province
carcinogenicity limits**

Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen
Bisphenol A - Epichlorohydrin polymer	-	-	-	-	-	-
Epoxy Resin Blend	-	-	-	-	-	-
Modified Silicone Dioxide	-	-	-	-	-	-
Elastomer Modified Diglycidal Ether	-	-	-	-	-	-
Cyclohexanedimethanol Diglycidyl Ether	-	-	-	-	-	-
Glycidoxypyrrol-Trimethoxysilane	-	-	-	-	-	-
Water, distilled, conductivity or of similar purity	-	-	-	-	-	-
Quartz (Crystalline Silica)	A2 - Suspected Human Carcinogen	ACGIH A2 IARC 1	ACGIH A2	-	ACGIH A2	C2 carcinogen
Methanol	-	-	-	-	-	-
Ethylene glycol	-	-	ACGIH A4	ACGIH A4	ACGIH A4	-
Carbon Black	-	IARC 2B	ACGIH A3	ACGIH A4	ACGIH A3	-
Calcium Carbonate	-	-	-	-	-	-

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish
Bisphenol A - Epichlorohydrin polymer	-	-
Epoxy Resin Blend	-	-
Modified Silicone Dioxide	-	-
Elastomer Modified Diglycidal Ether	-	-
Cyclohexanedimethanol Diglycidyl Ether	-	-
Glycidoxypyrrol-Trimethoxysilane	-	-
Water, distilled, conductivity or of similar purity	-	-
Quartz (Crystalline Silica)	-	-
Methanol	-	28200: 96 h Pimephales promelas mg/L LC50

Chemical name	Algae/aquatic plants	Fish
		flow-through 100: 96 h Pimephales promelas mg/L LC50 static 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through
Ethylene glycol	6500 - 13000: 96 h Pseudokirchneriella subcapitata mg/L EC50	41000: 96 h Oncorhynchus mykiss mg/L LC50 14 - 18: 96 h Oncorhynchus mykiss mL/L LC50 static 40761: 96 h Oncorhynchus mykiss mg/L LC50 static 40000 - 60000: 96 h Pimephales promelas mg/L LC50 static 27540: 96 h Lepomis macrochirus mg/L LC50 static 16000: 96 h Poecilia reticulata mg/L LC50 static
Carbon Black	-	-
Calcium Carbonate	-	-

Persistence and degradability No data available.

Bioaccumulation

Chemical name	CAS-No	Partition coefficient (log Kow)
Bisphenol A - Epichlorohydrin polymer 25068-38-6	25068-38-6	-
Epoxy Resin Blend Mixture	Mixture	-
Modified Silicone Dioxide 67762-90-7	67762-90-7	-
Elastomer Modified Diglycidyl Ether 163440-98-0	163440-98-0	-
Cyclohexanedimethanol Diglycidyl Ether 14228-73-0	14228-73-0	-
Glycidoxypropyl-Trimethoxysilane 2530-83-8	2530-83-8	-
Water, distilled, conductivity or of similar purity 7732-18-5	7732-18-5	-
Quartz (Crystalline Silica) 14808-60-7	14808-60-7	-
Methanol 67-56-1	67-56-1	-0.77
Ethylene glycol 107-21-1	107-21-1	-1.93
Carbon Black 1333-86-4	1333-86-4	-
Calcium Carbonate 1317-65-3	1317-65-3	-

Mobility in soil Not available.

Other adverse effects None known

13. DISPOSAL CONSIDERATIONS

Disposal information Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Dispose of all product, residues and clean-up materials in accordance with

local, state, and federal regulations.

Contaminated packaging Dispose in accordance with local, state and federal regulations.

14. TRANSPORTATION INFORMATION

Shipping Descriptions

DOT

ID-No UN3082
Proper shipping name Environmentally hazardous substance, liquid, n.o.s (bisphenolA(chloro)oxirane polymer)
Hazard Class(es) 9
Packing group III
Marine pollutant Yes.
Special Provisions LTD QTY

TDG

ID-No UN3082
Proper shipping name Environmentally hazardous substance, liquid, n.o.s (bisphenolA(chloro)oxirane polymer)
Hazard Class(es) 9
Packing group III
Marine pollutant Yes.
Special Provisions LTD QTY

IATA

ID-No UN3082
Proper shipping name Environmentally hazardous substance, liquid, n.o.s (bisphenolA(chloro)oxirane polymer)
Hazard Class(es) 9
Packing group III
Special Provisions LTD QTY

IMDG/IMO

ID-No UN3082
Proper shipping name Environmentally hazardous substance, liquid, n.o.s (bisphenolA(chloro)oxirane polymer)
Hazard Class(es) 9
Packing group III
EmS No F-A, S-F
Marine pollutant Yes
Special Provisions LTD QTY

Marine Pollutants

Chemical name	CAS-No	USDOT Marine Pollutant	Canada TDG Marine Pollutant	IMDG Marine Pollutant
Bisphenol A - Epichlorohydrin polymer	25068-38-6	-	-	-
Epoxy Resin Blend	Mixture	-	-	-
Modified Silicone Dioxide	67762-90-7	-	-	-
Elastomer Modified Diglycidal Ether	163440-98-0	-	-	-
Cyclohexanedimethanol Diglycidyl Ether	14228-73-0	-	-	-
Glycidoxypropyl-Trimethoxysilane	2530-83-8	-	-	-
Water, distilled, conductivity or of similar purity	7732-18-5	-	-	-
Quartz (Crystalline Silica)	14808-60-7	-	-	-
Methanol	67-56-1	-	-	-
Ethylene glycol	107-21-1	-	-	-
Carbon Black	1333-86-4	-	-	-
Calcium Carbonate	1317-65-3	-	-	-

Special Precautions Multi-modal shipping descriptions are provided for informational purposes and do not

consider container size. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

15. REGULATORY INFORMATION

State regulations

U.S. state Right-to-Know regulations

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Bisphenol A - Epichlorohydrin polymer	25068-38-6	-	-	-
Epoxy Resin Blend	Mixture	-	-	-
Modified Silicone Dioxide	67762-90-7	-	-	-
Elastomer Modified Diglycidal Ether	163440-98-0	-	-	-
Cyclohexanedimethanol Diglycidyl Ether	14228-73-0	-	-	-
Glycidoxypropyl-Trimethoxysilane	2530-83-8	-	-	-
Water, distilled, conductivity or of similar purity	7732-18-5	-	-	X
Quartz (Crystalline Silica)	14808-60-7	X	X	X
Methanol	67-56-1	X	X	X
Ethylene glycol	107-21-1	X	X	X
Carbon Black	1333-86-4	X	X	X
Calcium Carbonate	1317-65-3	X	X	X

California Prop. 65

WARNING: This product contains a chemical(s) known to the state of California to cause cancer

Chemical name	CAS-No	California Prop. 65
Bisphenol A - Epichlorohydrin polymer	25068-38-6	-
Epoxy Resin Blend	Mixture	-
Modified Silicone Dioxide	67762-90-7	-
Elastomer Modified Diglycidal Ether	163440-98-0	-
Cyclohexanedimethanol Diglycidyl Ether	14228-73-0	-
Glycidoxypropyl-Trimethoxysilane	2530-83-8	-
Water, distilled, conductivity or of similar purity	7732-18-5	-
Quartz (Crystalline Silica)	14808-60-7	Carcinogen
Methanol	67-56-1	Developmental
Ethylene glycol	107-21-1	Developmental
Carbon Black	1333-86-4	Carcinogen
Calcium Carbonate	1317-65-3	-

U.S. Federal Regulations

US EPA SARA 313

Chemical name	CAS-No	CERCLA/SARA Hazardous Substances RQ	SARA 313 - Threshold Values
---------------	--------	-------------------------------------	-----------------------------

Chemical name	CAS-No	CERCLA/SARA Hazardous Substances RQ	SARA 313 - Threshold Values
Bisphenol A - Epichlorohydrin polymer	25068-38-6	-	-
Epoxy Resin Blend	Mixture	-	-
Modified Silicone Dioxide	67762-90-7	-	-
Elastomer Modified Diglycidal Ether	163440-98-0	-	-
Cyclohexanedimethanol Diglycidyl Ether	14228-73-0	-	-
Glycidoxypropyl-Trimethoxysilane	2530-83-8	-	-
Water, distilled, conductivity or of similar purity	7732-18-5	-	-
Quartz (Crystalline Silica)	14808-60-7	-	-
Methanol	67-56-1	5000 lb 2270 kg	1.0 %
Ethylene glycol	107-21-1	5000 lb 2270 kg	1.0 %
Carbon Black	1333-86-4	-	-
Calcium Carbonate	1317-65-3	-	-

**US EPA SARA 311/312
hazardous categorization**

Not available

Chemical name	DSL/NDSL	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification
Bisphenol A - Epichlorohydrin polymer	X	X	-
Epoxy Resin Blend	-	-	-
Modified Silicone Dioxide	X	X	-
Elastomer Modified Diglycidal Ether	X	X	-
Cyclohexanedimethanol Diglycidyl Ether	X	X	-
Glycidoxypropyl-Trimethoxysilane	X	X	-
Water, distilled, conductivity or of similar purity	X	X	-
Quartz (Crystalline Silica)	X	X	-
Methanol	X	X	-
Ethylene glycol	X	X	-
Carbon Black	X	X	-
Calcium Carbonate	X	X	-

Legend X - Listed

16. OTHER INFORMATION

NFPA

Health	2
Flammability	1
Instability	0

HMIS

Health	2
Flammability	1

Physical hazards 0

Notice: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA).

Prepared by Regulatory Affairs

Issue date 05-Apr-2019

Revision date 05-Apr-2019

Revision note

Key to abbreviations

ACGIH (American Conference of Governmental Industrial Hygienists)
ATE (Average Toxicity Estimate)
DSL/NDSL (Domestic Substance List/Non-Domestic Substance List)
HMIS (Hazardous Materials Identification System)
IARC (International Agency for Research on Cancer)
IATA (International Air Transport Association)
IMDG/IMO (International Maritime Dangerous Goods/International Maritime Organization)
NFPA (National Fire Protection Association)
NTP (National Toxicology Program)
OEL (Occupational Exposure Level)
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
PEL (Permissible Exposure Limit)
TSCA (Toxic Substance Control Act)
USEPA (United States Environmental Protection Agency)

Disclaimer

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

End of Safety Data Sheet