



Safety Data Sheet

Issue date 17-Jul-2018

Revision date 17-Jul-2018

Revision Number 1

1. IDENTIFICATION

Product identification

Product identifier Kent® Quick Seal 2000 Gray Sprayable Seam Sealer

Other means of identification P13706

Recommended use Sealant

Restrictions on use For industrial use only

Supplier

Corporate Headquarters:
Kent Automotive
8770 W. Bryn Mawr Ave.- Suite 900
Chicago, IL 60631
(888)-937-5368

Canadian Distribution Center:
Lawson Canada
7315 Rapistan Court
Mississauga, ON L5N 5Z4
(800) 323-5922

24 Hour Emergency Phone Number (888) 426-4851 (Prosar)

2. HAZARD(S) IDENTIFICATION

Hazard Classification This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Skin sensitization	Category 1
Flammable liquids	Category 3

Symbol



Signal word WARNING

Hazard statements H317 - May cause an allergic skin reaction

Precautionary statements

General	P101 - If medical advice is needed, have product container or label at hand P102 - Keep out of reach of children P103 - Read label before use.
Prevention	P233 - Keep container tightly closed P240 - Ground/bond container and receiving equipment P241 - Use explosion-proof electrical/ ventilating/ lighting/ equipment P242 - Use only non-sparking tools P243 - Take precautionary measures against static discharge P261 - Avoid breathing dust/fume/gas/mist/vapors/spray P272 - Contaminated work clothing should not be allowed out of the workplace P280 - Wear protective gloves/protective clothing and eye/face protection P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Response	
General	P321 - For Specific treatment see section 4 of this sds
Eyes	P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Skin	P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention P363 - Wash contaminated clothing before reuse P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Inhalation	P340 - Remove victim to fresh air and keep at rest in a position comfortable for breathing
Ingestion	P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting P314 - Get medical advice/attention if you feel unwell
Fire	P370 + P378 - In case of fire: Use appropriate method to extinguish
Spill	P391 - Collect spillage
Storage	P404 - Store in a closed container P233 - Keep container tightly closed P403 + P235 - Store in a well-ventilated place. Keep cool
Disposal	P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable
Hazard(s) Not Otherwise Classified (HNOC)	Not available.
Physical Hazards Not Otherwise Classified (PHNOC)	Not available.
Unknown acute toxicity	5.24%

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition Mixture.

Chemical name	CAS-No	Weight %
---------------	--------	----------

Limestone	1317-65-3	15-40
Calcium Carbonate	471-34-1	10-30
Trimethoxyvinylsilane	2768-02-7	1-5
Titanium Dioxide	13463-67-7	1-5
Stoddard solvent	8052-41-3	1-5
Octadecanoic acid	57-11-4	1-5
Tin, dibutylbis(2,4-pentanedionato-O,O'')-, (OC-6-11)-	22673-19-4	0.1-1
N-beta (aminoethyl) gamma-aminopropyltrimethoxysilane	1760-24-3	0.1-1
Carbon Black	1333-86-4	0.1-1
Methanol	67-56-1	<1
Diisodecyl Phthalate	68515-49-1	<1
Di-isonyl phthalate	68515-48-0	<1

4. FIRST-AID MEASURES

Necessary first-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical advice and bring MSDS or label.
Ingestion	Do NOT induce vomiting. Rinse mouth. Do not give anything by mouth to an unconscious person. Seek medical advice and bring MSDS or label.
Skin contact	Wash contaminated skin with soap and water. Remove contaminated clothing. If skin irritation persists, call a physician.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Hold eyelids apart and consult a physician.
Most important symptoms (acute)	Not available.
Most important symptoms (over-exposure)	No known significant effects or critical hazards.
Indication of any immediate medical attention and special treatment needed	Treat symptomatically. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	In case of fire, use water spray (fog), foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	Full water jet.
Specific hazards	Thermal decomposition can lead to release of toxic/corrosive gases and vapors. Hazardous Thermal Decomposition Products: Carbon dioxide. Carbon monoxide.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with full face-piece operated in positive pressure mode. Do not allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	Wear personal protective equipment. Avoid contact with eyes, skin, and clothing. Prevent entry into waterways, sewers, basements, and confined areas. Do not allow to enter into
------------------------------	--

protective equipment and emergency procedures

soil/subsoil.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Take precautionary measures against static discharges.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin, eyes and clothing. Put on appropriate personal protective equipment.

Conditions for safe storage, including any incompatibilities

Keep in a dry, cool and well-ventilated place. Keep away from food, beverages, and feed. Keep container tightly closed. Recommended storage temperature 10-35°C. Protect from moisture.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical name	OSHA PEL (TWA)	ACGIH OEL (TWA)	NIOSH - TWA
Limestone	15 mg/m ³ TWA 5 mg/m ³ TWA	-	10 mg/m ³ TWA 5 mg/m ³ TWA
Calcium Carbonate	15 mg/m ³ TWA 5 mg/m ³ TWA	-	10 mg/m ³ TWA 5 mg/m ³ TWA 10 mg/m ³ TWA 5 mg/m ³ TWA
Trimethoxyvinylsilane	-	-	-
Titanium Dioxide	15 mg/m ³ TWA	10 mg/m ³ TWA	-
Stoddard solvent	500 ppm TWA 2900 mg/m ³ TWA	100 ppm TWA	350 mg/m ³ TWA
Octadecanoic acid	-	10 mg/m ³ TWA 3 mg/m ³ TWA	-
Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-	0.1 mg/m ³ TWA	0.2 mg/m ³ STEL 0.1 mg/m ³ TWA Skin	0.1 mg/m ³ TWA
N-beta (aminoethyl) gamma-aminopropyltrimethoxysilane	-	-	-
Carbon Black	3.5 mg/m ³ TWA	3 mg/m ³ TWA	3.5 mg/m ³ TWA 0.1 mg/m ³ TWA
Methanol	200 ppm TWA 260 mg/m ³ TWA	250 ppm STEL 200 ppm TWA Skin	250 ppm STEL 325 mg/m ³ STEL 200 ppm TWA 260 mg/m ³ TWA
Diisodecyl Phthalate	-	-	-
Di-isonyl phthalate	-	-	-

Appropriate engineering controls

A safety shower and eye wash station should be available for emergency use. Adequate ventilation should be provided to keep exposure levels below current acceptable exposure limits.

Individual protection measures, such as personal protective equipment

Eye protection

Tightly fitting safety goggles.

Skin and body protection

For prolonged or repeated skin contact, use a chemically resistant glove such as nitrile or neoprene. Wash hands with soap and water after removing gloves. Dry hands thoroughly before re-applying gloves.

Respiratory protection

If vapors are present or irritation is experienced, use a NIOSH/MSHA approved respirator. An air supplied, positive pressure respirator may be required if working conditions do not provide adequate ventilation to keep exposures below the limits. Wear a NIOSH approved air purifying organic cartridge respirator.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. When using, do not eat, drink or smoke. Avoid contact with skin, eyes and clothing. Wash area thoroughly with soap and water. Remove and wash contaminated clothing before re-use.

Canadian Province Occupational Exposure Limits

Chemical name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick - OEL	Newfoundland and Labrador - OEL	Nova Scotia - OEL	Ontario OEL	Prince Edward Island - OEL	Quebec OEL	Saskatchewan - OEL
Limestone	10 mg/m ³ TWA	20 mg/m ³ STEL 10 mg/m ³ TWA 3 mg/m ³ TWA	-	10 mg/m ³ TWA	-	-	-	-	10 mg/m ³ TWA EV	20 mg/m ³ STEL 10 mg/m ³ TWA
Calcium Carbonate	10 mg/m ³ TWA	20 mg/m ³ STEL 10 mg/m ³ TWA 3 mg/m ³ TWA	-	10 mg/m ³ TWA	-	-	-	-	10 mg/m ³ TWA EV 10 mg/m ³ TWA EV	20 mg/m ³ STEL 10 mg/m ³ TWA 10 mg/m ³ TWA
Trimethoxyvinylsilane	-	-	-	-	-	-	10 ppm STEL 60 mg/m ³ STEL	-	-	-
Titanium Dioxide	10 mg/m ³ TWA	10 mg/m ³ TWA 3 mg/m ³ TWA	10 mg/m ³ TWA	10 mg/m ³ TWA	10 mg/m ³ TWA	10 mg/m ³ TWA	10 mg/m ³ TWA	10 mg/m ³ TWA	10 mg/m ³ TWA EV	20 mg/m ³ STEL 10 mg/m ³ TWA
Stoddard solvent	100 ppm TWA 572 mg/m ³ TWA	580 mg/m ³ STEL 290 mg/m ³ TWA	100 ppm TWA	100 ppm TWA 525 mg/m ³ TWA	100 ppm TWA	100 ppm TWA	525 mg/m ³ TWA	100 ppm TWA	100 ppm TWA EV 525 mg/m ³ TWA EV	125 ppm STEL 100 ppm TWA
Octadecanoic acid	-	-	10 mg/m ³ TWA 3 mg/m ³ TWA	-	10 mg/m ³ TWA 3 mg/m ³ TWA	10 mg/m ³ TWA 3 mg/m ³ TWA	-	10 mg/m ³ TWA 3 mg/m ³ TWA	-	-
Tin, dibutylbis(2,4-pentanedionato-O,O'-), (OC-6-11)-	0.2 mg/m ³ STEL 0.1 mg/m ³ TWA	0.2 mg/m ³ STEL 0.1 mg/m ³ TWA	0.1 mg/m ³ TWA 0.2 mg/m ³ STEL	0.2 mg/m ³ STEL 0.1 mg/m ³ TWA	0.2 mg/m ³ STEL 0.1 mg/m ³ TWA	0.2 mg/m ³ STEL 0.1 mg/m ³ TWA	0.2 mg/m ³ STEL 0.1 mg/m ³ TWA	0.2 mg/m ³ STEL 0.1 mg/m ³ TWA	0.2 mg/m ³ STEL 0.1 mg/m ³ TWA EV	0.2 mg/m ³ STEL 0.1 mg/m ³ TWA
N-beta (aminoethyl) gamma-aminopropyltrimethoxysilane	-	-	-	-	-	-	-	-	-	-
Carbon Black	3.5 mg/m ³ TWA	3 mg/m ³ TWA	3 mg/m ³ TWA	3.5 mg/m ³ TWA	3 mg/m ³ TWA	3 mg/m ³ TWA	3 mg/m ³ TWA	3 mg/m ³ TWA	3.5 mg/m ³ TWA EV	7 mg/m ³ STEL 3.5 mg/m ³ TWA
Methanol	250 ppm STEL 328 mg/m ³ STEL 200 ppm TWA 262 mg/m ³ TWA	250 ppm STEL 200 ppm TWA	200 ppm TWA 250 ppm STEL	250 ppm STEL 328 mg/m ³ STEL 200 ppm TWA 262 mg/m ³ TWA	250 ppm STEL 200 ppm TWA	250 ppm STEL 200 ppm TWA	250 ppm STEL 200 ppm TWA	250 ppm STEL 200 ppm TWA	250 ppm STEL 328 mg/m ³ STEL 200 ppm TWA EV 262 mg/m ³ TWA EV	250 ppm STEL 200 ppm TWA
Diisodecyl Phthalate	-	-	-	-	-	-	-	-	-	-

Chemical name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick - OEL	Newfoundl and & Labrador - OEL	Nova Scotia - OEL	Ontario OEL	Prince Edward Island - OEL	Quebec OEL	Saskatche wan - OEL
Di-isonyl phthalate	-	-	-	-	-	-	-	-	-	-

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid Paste
Color	Gray
Odor	Not available
Odor threshold	Not available
pH	No data available
Melting point/range °C	No data available
Melting point/range °F	No data available
Boiling point/range °C	No data available
Boiling point/range °F	No data available
Flash point °C	38.3
Flash point °F	100.9
Flash point method used	Not available
Evaporation rate	No data available
Flammability (Solid, Gas)	No data available
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor pressure	No data available
Vapor density	No data available
Relative density	1.39 - 1.64
Solubility	Not available
Partition coefficient (n-octanol/water)	No data available
Autoignition temperature °C	No data available
Autoignition temperature °F	No data available
Decomposition temperature °C	No data available
Decomposition temperature °F	No data available

Viscosity No data available

10. STABILITY AND REACTIVITY

Reactivity No dangerous reactions under normal conditions of use.

Chemical stability Stable under recommended storage conditions.

Possibility of hazardous reactions None under normal conditions of use.

Conditions to avoid Heat, flames and sparks.

Incompatible materials None known based on information supplied.

Hazardous decomposition products None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure Dermal. Inhalation. Ingestion. Eyes.

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure Target Organ Effects: Central nervous system. Eyes. Kidney. Lungs. Respiratory system. Skin.

Numerical measures of toxicity

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:
Limestone	-	-	-
Calcium Carbonate	-	-	= 6450 mg/kg (Rat)
Trimethoxyvinylsilane	-	= 3360 µL/kg (Rabbit)	= 7340 µL/kg (Rat)
Titanium Dioxide	-	-	> 10000 mg/kg (Rat)
Stoddard solvent	-	-	-
Octadecanoic acid	-	> 5 g/kg (Rabbit)	= 4600 mg/kg (Rat) = 3200 mg/kg (Rat) > 5000 mg/kg (Rat)
Tin, dibutylbis(2,4-pentanedionato-O,O")-, (OC-6-11)-	-	-	-
N-beta (aminoethyl) gamma-aminopropyltrimethoxysilane	-	-	= 2413 mg/kg (Rat) = 7460 µL/kg (Rat)
Carbon Black	-	> 3 g/kg (Rabbit)	> 15400 mg/kg (Rat)
Methanol	= 22500 ppm (Rat) 8 h = 64000 ppm (Rat) 4 h	= 15800 mg/kg (Rabbit) = 15840 mg/kg (Rabbit)	= 6200 mg/kg (Rat)
Diisodecyl Phthalate	-	= 16000 mg/kg (Rabbit)	> 60000 mg/kg (Rat)
Di-isonyl phthalate	-	> 3160 mg/kg (Rabbit)	> 10000 mg/kg (Rat)

ATEmix (dermal) Not available

ATEmix (oral) Not available

ATEmix (inhalation-gas) Not available

ATEmix (inhalation-vapor) Not available

ATEmix (inhalation-dust/mist) Not available

Carcinogenicity

Chemical name	ACGIH OEL - Carcinogens	IARC	OSHA RTK Carcinogens	NTP
Limestone	-	-	-	-
Calcium Carbonate	-	-	-	-
Trimethoxyvinylsilane	-	-	-	-
Titanium Dioxide	A4	Group 2B	Listed	-
Stoddard solvent	-	-	-	-
Octadecanoic acid	-	-	-	-
Tin, dibutylbis(2,4-pentanedionato-O,O")-, (OC-6-11)-	A4	-	-	-
N-beta (aminoethyl) gamma-aminopropyltrimethoxysilane	-	-	-	-
Carbon Black	A3	Group 2B	Listed	-
Methanol	-	-	-	-
Diisodecyl Phthalate	-	-	-	-
Di-isonyl phthalate	-	-	-	-

Canadian Province carcinogenicity limits

Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen
Limestone	-	-	-	-	-	-
Calcium Carbonate	-	-	-	-	-	-
Trimethoxyvinylsilane	-	-	-	-	-	-
Titanium Dioxide	-	IARC 2B	ACGIH A4	ACGIH A4	ACGIH A4	-
Stoddard solvent	-	-	-	-	-	-
Octadecanoic acid	-	-	-	-	-	-
Tin, dibutylbis(2,4-pentanedionato-O,O")-, (OC-6-11)-	-	-	ACGIH A4	ACGIH A4	ACGIH A4	-
N-beta (aminoethyl) gamma-aminopropyltrimethoxysilane	-	-	-	-	-	-
Carbon Black	-	IARC 2B	ACGIH A3	ACGIH A4	ACGIH A3	-
Methanol	-	-	-	-	-	-
Diisodecyl Phthalate	-	-	-	-	-	-
Di-isonyl phthalate	-	-	-	-	-	-

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish
Limestone	-	-
Calcium Carbonate	-	-
Trimethoxyvinylsilane	-	-
Titanium Dioxide	-	-
Stoddard solvent	-	-
Octadecanoic acid	-	3000: 96 h Brachydanio rerio mg/L LC50 semi-static
Tin, dibutylbis(2,4-pentanedionato-O,O"), (OC-6-11)-	-	-
N-beta (aminoethyl) gamma-aminopropyltrimethoxysilane	-	-
Carbon Black	-	-
Methanol	-	100: 96 h Pimephales promelas mg/L LC50 static 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 28200: 96 h Pimephales promelas mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static
Diisodecyl Phthalate	1.3: 96 h Pseudokirchneriella subcapitata mg/L EC50	1: 96 h Oncorhynchus mykiss mg/L LC50 static 0.66: 96 h Pimephales promelas mg/L LC50 static 1: 96 h Pimephales promelas mg/L LC50 flow-through 0.62: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.55: 96 h Lepomis macrochirus mg/L LC50 static
Di-isonyl phthalate	2.8: 96 h Pseudokirchneriella subcapitata mg/L EC50	0.42: 96 h Ictalurus punctatus mg/L LC50 flow-through 0.16: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.17: 96 h Lepomis macrochirus mg/L LC50 static 0.14: 96 h Pimephales promelas mg/L LC50 static 0.19: 96 h Pimephales promelas mg/L LC50 flow-through

Persistence and degradability No data available.

Bioaccumulation No information available

Chemical name	CAS-No	Partition coefficient (log Kow)
Limestone 1317-65-3	1317-65-3	-
Calcium Carbonate 471-34-1	471-34-1	-
Trimethoxyvinylsilane 2768-02-7	2768-02-7	-
Titanium Dioxide 13463-67-7	13463-67-7	-
Stoddard solvent 8052-41-3	8052-41-3	-
Octadecanoic acid 57-11-4	57-11-4	-
Tin, dibutylbis(2,4-pentanedionato-O,O"), (OC-6-11)- 22673-19-4	22673-19-4	-
N-beta (aminoethyl) gamma-aminopropyltrimethoxysilane	1760-24-3	-

Chemical name	CAS-No	Partition coefficient (log Kow)
1760-24-3		
Carbon Black 1333-86-4	1333-86-4	-
Methanol 67-56-1	67-56-1	-0.77
Diisodecyl Phthalate 68515-49-1	68515-49-1	-
Di-isonyl phthalate 68515-48-0	68515-48-0	-

Mobility in soil Not available.

Other adverse effects Not available

13. DISPOSAL CONSIDERATIONS

Disposal information Dispose of all product, residues and clean-up materials in accordance with local, state, and federal regulations.

Contaminated packaging Dispose in accordance with local, state and federal regulations.

14. TRANSPORTATION INFORMATION

Shipping Descriptions

DOT

ID-No UN1133
Proper shipping name Adhesives
Hazard Class(es) 3
Packing group III
Special Provisions LTD QTY

TDG

ID-No UN1133
Proper shipping name Adhesives
Hazard Class(es) 3
Packing group III
Special Provisions LTD QTY

IATA

ID-No UN1133
Proper shipping name Adhesives
Hazard Class(es) 3
Packing group III

IMDG/IMO

ID-No UN1133
Proper shipping name Adhesives
Hazard Class(es) 3
Packing group III
EmS No F-E, S-D
Special Provisions LTD QTY, 223, 955

Marine Pollutants

Chemical name	CAS-No	USDOT Marine Pollutant	Canada TDG Marine Pollutant	IMDG Marine Pollutant
---------------	--------	---------------------------	--------------------------------	--------------------------

Chemical name	CAS-No	USDOT Marine Pollutant	Canada TDG Marine Pollutant	IMDG Marine Pollutant
Limestone	1317-65-3	-	-	-
Calcium Carbonate	471-34-1	-	-	-
Trimethoxyvinylsilane	2768-02-7	-	-	-
Titanium Dioxide	13463-67-7	-	-	-
Stoddard solvent	8052-41-3	X	-	-
Octadecanoic acid	57-11-4	-	-	-
Tin, dibutylbis(2,4-pentanedionato-O,O")-, (OC-6-11)-	22673-19-4	X	-	-
N-beta (aminoethyl) gamma-aminopropyltrimethoxysilane	1760-24-3	-	-	-
Carbon Black	1333-86-4	-	-	-
Methanol	67-56-1	-	-	-
Diisodecyl Phthalate	68515-49-1	-	-	-
Di-isonyl phthalate	68515-48-0	-	-	-

Special Precautions

Multi-modal shipping descriptions are provided for informational purposes and do not consider container size. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

15. REGULATORY INFORMATION

State regulations

U.S. state Right-to-Know regulations

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Limestone	1317-65-3	X	X	X
Calcium Carbonate	471-34-1	X	X	X
Trimethoxyvinylsilane	2768-02-7	-	-	-
Titanium Dioxide	13463-67-7	X	X	X
Stoddard solvent	8052-41-3	X	X	X
Octadecanoic acid	57-11-4	-	-	-
Tin, dibutylbis(2,4-pentanedionato-O,O")-, (OC-6-11)-	22673-19-4	-	-	-
N-beta (aminoethyl) gamma-aminopropyltrimethoxysilane	1760-24-3	-	-	-
Carbon Black	1333-86-4	X	X	X
Methanol	67-56-1	X	X	X
Diisodecyl Phthalate	68515-49-1	-	-	X
Di-isonyl phthalate	68515-48-0	-	-	X

California Prop. 65

WARNING: This product contains a chemical(s) known to the state of California to cause cancer, birth defects or other reproductive harm

Chemical name	CAS-No	California Prop. 65
Limestone	1317-65-3	-

Chemical name	CAS-No	California Prop. 65
Calcium Carbonate	471-34-1	-
Trimethoxyvinylsilane	2768-02-7	-
Titanium Dioxide	13463-67-7	Carcinogen
Stoddard solvent	8052-41-3	-
Octadecanoic acid	57-11-4	-
Tin, dibutylbis(2,4-pentanedionato-O,O'')-, (OC-6-11)-	22673-19-4	-
N-beta (aminoethyl) gamma-aminopropyltrimethoxysilane	1760-24-3	-
Carbon Black	1333-86-4	Carcinogen
Methanol	67-56-1	Developmental
Diisodecyl Phthalate	68515-49-1	Developmental
Di-isonyl phthalate	68515-48-0	Carcinogen

U.S. Federal Regulations

US EPA SARA 313

Chemical name	CAS-No	CERCLA/SARA Hazardous Substances RQ	SARA 313 - Threshold Values
Limestone	1317-65-3	-	-
Calcium Carbonate	471-34-1	-	-
Trimethoxyvinylsilane	2768-02-7	-	-
Titanium Dioxide	13463-67-7	-	-
Stoddard solvent	8052-41-3	-	-
Octadecanoic acid	57-11-4	-	-
Tin, dibutylbis(2,4-pentanedionato-O,O'')-, (OC-6-11)-	22673-19-4	-	-
N-beta (aminoethyl) gamma-aminopropyltrimethoxysilane	1760-24-3	-	-
Carbon Black	1333-86-4	-	-
Methanol	67-56-1	5000 lb 2270 kg	1.0 %
Diisodecyl Phthalate	68515-49-1	-	-
Di-isonyl phthalate	68515-48-0	-	-

US EPA SARA 311/312 hazardous categorization

Not available

International inventories

All components of this product are listed on the following inventories: U.S.A. (TSCA 8(b)), Canada (DSL/NDSL) or are exempt.

Chemical name	DSL/NDSL	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification
Limestone	X	X	-
Calcium Carbonate	X	X	-
Trimethoxyvinylsilane	X	X	-
Titanium Dioxide	X	X	-
Stoddard solvent	X	X	-
Octadecanoic acid	X	X	-

Chemical name	DSL/NDSL	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification
Tin, dibutylbis(2,4-pentanedionato-O,O")-, (OC-6-11)-	X	X	-
N-beta (aminoethyl) gamma-aminopropyltrimethoxysilane	X	X	-
Carbon Black	X	X	-
Methanol	X	X	-
Diisodecyl Phthalate	X	X	-
Di-isonyl phthalate	X	X	-

Legend X - Listed

16. OTHER INFORMATION

NFPA

Health	Not available
Flammability	Not available
Instability	Not available

HMIS

Health	2
Flammability	2
Physical hazards	1
Personal protection	X

Notice: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA).

Prepared by Regulatory Affairs

Issue date 17-Jul-2018

Revision date 17-Jul-2018

Revision note

Key to abbreviations

ACGIH (American Conference of Governmental Industrial Hygienists)
 ATE (Average Toxicity Estimate)
 DSL/NDSL (Domestic Substance List/Non-Domestic Substance List)
 HMIS (Hazardous Materials Identification System)
 IARC (International Agency for Research on Cancer)
 IATA (International Air Transport Association)
 IMDG/IMO (International Maritime Dangerous Goods/International Maritime Organization)
 NFPA (National Fire Protection Association)
 NTP (National Toxicology Program)
 OEL (Occupational Exposure Level)
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 PEL (Permissible Exposure Limit)
 TSCA (Toxic Substance Control Act)

USEPA (United States Environmental Protection Agency)

Disclaimer

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

End of Safety Data Sheet